




Operator
Telephone
Fax
e-Mail

Кота +6,20-Читалня-Детски отдел / Single Sheet Output



Height of Room: 4.850 m, Mounting Height: 4.850 m, Maintenance factor: 0.80

Values in Lux, Scale 1:98

Surface	ρ [%]	E_{av} [lx]	E_{min} [lx]	E_{max} [lx]	u_0
Workplane	/	489	358	567	0.731
Floor	20	406	272	494	0.669
Ceiling	70	126	91	153	0.725
Walls (4)	50	287	113	527	/

Workplane:

Height: 0.750 m
Grid: 32 x 32 Points
Boundary Zone: 0.500 m

Illuminance Quotient (according to LG7): Walls / Working Plane: 0.609, Ceiling / Working Plane: 0.257.

Luminaire Parts List

No.	Pieces	Designation (Correction Factor)	Φ (Luminaire) [lm]	Φ (Lamps) [lm]	P [W]
1	10	OCTA-LIGHT PLC OCTL_OLOT_S-40RNWR-230 (1.000)	4772	4800	40.0
Total:			47722	48000	400.0

Specific connected load: $7.95 \text{ W/m}^2 = 1.62 \text{ W/m}^2/100 \text{ lx}$ (Ground area: 50.31 m^2)